

Product Data

CRB Multi 20W-50 CF-4

For long and healthy engine life

Description

Castrol CRB Multi 20W-50 CF-4 is a multi-purpose, heavy duty diesel engine oil. It is suitable for use in naturally-aspirated, turbocharged or supercharged diesel engines that use a broad range of fuel qualities.

Advantages

During its working life, your engine faces challenges from combustion by-products that can form deposits, and thicken the oil. Castrol CRB Multi 20W-50 CF-4 helps combat these issues in two ways:

- 1. It contains cleaning agents which help to displace particles that may otherwise build up on your engine surfaces reducing deposits.
- 2. It also contains anti-oxidants which help to disrupt the chemical reactions that can lead to oil thickening.

Castrol CRB Multi 20W-50 CF-4 helps provide protection across multiple applications to encourage long and healthy engine life.

Typical Characteristics

| Name | Method | Units | CRB Multi 20W-40 CF-4 |
|---------------------------|------------|------------|-----------------------|
| Density @ 15C | ASTM D4052 | g/ml | 0.880 |
| Viscosity, Kinematic 100C | ASTM D445 | mm²/s | 18.5 |
| Viscosity, CCS -15C (20W) | ASTM D5293 | mPa.s (cP) | 5700 |
| Viscosity, Kinematic 40C | ASTM D445 | mm²/s | 160 |
| Viscosity Index | ASTM D2270 | None | 130 |
| Ash, Sulphated | ASTM D874 | % wt | 1.4 |
| Total Base Number, TBN | ASTM D2896 | mg KOH/g | 9.9 |
| Pour Point | ASTM D97 | °C | -42 |
| Flash Point, PMCC | ASTM D93 | °C | 210 |

Product Performance Claims

API CF-4

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

CRB Multi 20W-50 CF-4 07 Jul 2020